

E-Lack S3885

Typ: NC-Emulsionslack
solventverdünnt,
schwarz pigmentiert

Type: *NC emulsion lacquer
solvent thinnable,
black pigmented*

Festkörper: ca. 12%

Solid content: *approx. 12%*

Flammpunkt: ca. 45°C

Flashpoint: *approx. 45°C*

Eigenschaften: E-Lack S3885 ist eine schwarz pigmentierte Lackemulsion mit guter Füllwirkung, die eine gute Oberflächenruhe bringt. Man erzielt einen tiefen Schwarzgrad und seidenglänzendes Aussehen.

Die DLH E-Lack S Reihe sind Emulsionen von Nitrozellulose und Cellulosederivaten in organischen Lösungsmitteln. Als Verdünnung wird eine Mischung von Butylacetat : Spiritus = 6:4 empfohlen.

Properties: *E-Lack S3885 is a black pigmented silky lustre emulsion lacquer with a good build and a uniform smooth surface, producing a deep black tone.*

DLH E-Lack S (solvent) types are emulsions of nitro-cellulose and cellulose derivatives in organic solvents. For thinning a mixture of butyl acetate : ethyl alcohol = 6:4 is recommended.

Lagerung: +2°C to +30°C
frostfest
UN2059 ADR Kl.3 Zi.33c

Storage: +2°C to +30°C
frostproof
UN2059 ADR Cl.3 Cf.33c

Lagerzeit: 6 Monate
in gut verschlossenem Gebinde.

Shelf life: *6 months*
in well sealed containers.

Vor Gebrauch gut aufrühren.

Stir well before use.