

Mattierlack S1900

Typ: NC-Emulsionslack
solventverdünntbar,
farblos, matt

Festkörper: ca. 22,5%

Flammpunkt: 12°C

Eigenschaften: Mattierlack S1900 ist ein gut mattierender, farbloser NC-Emulsionslack, der allein oder in Kombination mit DLH S-Lacken für matte Top-Coats eingesetzt werden kann.

Die DLH E-Lack S Reihe sind Emulsionen von Nitrozellulose und Cellulosederivaten in organischen Lösungsmitteln. Als Verdünnung wird eine Mischung von Butylacetat : Spiritus = 6:4 empfohlen.

Lagerung: +2°C to +30°C
frostfest
UN2059 ADR Ki.3 Zi.5b

Lagerzeit: 12 Monate
in gut verschlossenem Gebinde.

Vor Gebrauch gut aufrühren.

Type: NC emulsion lacquer
solvent thinnable,
colourless, mat

Solid content: approx. 22,5%

Flashpoint: 12°C

Properties: Mattierlack S1900 is a mat colourless NC emulsion, suitable to be used alone or in combination with other DLH solvent thinnable lacquers to achieve matted top coats.

DLH E-Lack S (solvent) types are emulsions of nitro-cellulose and cellulose derivatives in organic solvents. For thinning a mixture of butyl acetate : ethyl alcohol = 6:4 is recommended.

Storage: +2°C to +30°C
frostproof
UN2059 ADR Cl.3 Cf.5b

Shelf life: 12 months
in well sealed containers.

Stir well before use